App. No. 09/691325 Advisory Action Dated January 31, 2005 Amd. Dated March 9, 2005

Amendments to the Claims:

This listing of claims will replace all prior versions and listing of claims in the application.

Claims 14-19, 22, 24-29 and 32 are canceled without prejudice or disclaimer.

Listing of Claims:

- 1. (Previously Presented) A grout for watertight screens, which consists of water, a natural or modified clay, a blast furnace slag having a maximum grain size of between about 50 μ m and about 100 μ m and a Portland cement as an activating agent, wherein said grout has a cement/water ratio of between 0.1 and 0.25.
- (Original) The grout according to claim 1, in which the slag has a maximum grain size equal to about 80 μm.
- 3. (Previously Presented) The grout according to claim 1, in which the slag has a CaO/SiO₂ weight ratio of between 1.10 and 1.35.
- 4. (Previously Presented) The grout according to claim 1, in which the slag has a chemical modulus of greater than about 500.
- 5. (Previously Presented) The grout according to claim 1, in which the modified clay is bentonite.
- 6. (Canceled)
- 7. (Previously Presented) The grout according to claim 1, in which the amount of Portland cement is about 1% to about 10% by weight with respect to the weight of the blast furnace slag.
- 8-12. (Canceled)

App. No. 09/691325 Advisory Action Dated January 31, 2005 Amd. Dated March 9, 2005

13. (Previously Presented) The grout of claim 1, in which the slag has a Blaine specific surface area of about 2,500 to about 4,500 cm²/g.

14-38. (Canceled)